

High Pressure Glycerin Filled Pressure Gauges

"POINTER" High pressure Glycerin filled gauges are Specially for High Pressure Application & Testing of High Pressure Devices. It is Mfg. & Calibrate under Delectated (Imported) High Pressure System. It means Performance of the gauge enhance the reliable and integrated for long periods under extreme operating condition.



150mm Bottom Mounting



100mm Bottom Mounting



150mm Bottom Mounting

CONSTRUCTION FEATURES

Dial Size	: 100mm, 150mm & 250mm
Accuracy	: $\pm 1.6\%$ of full scale
Case & Bezel (IP-65)	: SS 304, Snap Action Bayonet type
Movement	: SS 304
Pressure Element	: SS 316
Socket	: SS 304 / SS316
Dial	: Aluminum white painted with 270 degree black scale marking
Pointer	: Al. / Brass with black finish
Window	: Acrylic / Safety glass
Blow Out Protection	: On top at 0.6 Kg/cm ²
Over Load Protection	: 115% of f.s.d.
Joints	: Argon arc welded
Mounting	: Stem (Bottom), Surface, Panel Mounting, Flush Panel (Bracket Type)
Connection	: 3/8" / 1/2" BSP / NPT
Scale Range	: Pressure up to 15000 PSI to 80000 PSI

MODEL OPTION

SP : All SS Models with Heavy Duty Parts.

APPLICATION

Specially in High Pressure Application, Hydraulic Pressure, Hydraulic Power Packs, High Pressure Pumps, Testing of High Pressure Devices.

POINTER INSTRUMENTS PVT. LTD.

210, Phase-1, G.I.D.C. Industrial Estate, Chhatral-382 729. Tal.: Kalol, Dist.: Gandhinagar, Gujarat, INDIA.
Ph.: +91 2764-234357 | E-mail: sales@pointer.in, pointer210@yahoo.co.in, info@pointer.in | Web: www.pointer.in

