

Single Diaphragm Differential Pressure Gauges

“POINTER” Differential pressure gauge is suitable for corrosive environment and gaseous media.



CONSTRUCTION FEATURES

Dial Size	: 100mm & 150mm.
Accuracy	: $\pm 1.6\%$ of full scale.
Case & Bezel (IP-65)	: SS 304 Snap Action Bayonet type.
Movement	: SS 304
Pressure Element	: SS 316L Single diaphragm.
HP / LP Chamber	: SS 304 / SS 316.
Dial	: Aluminum white painted with 270 degree black scale marking
Pointer	: Al. / Brass, Micro Zero Adjustment pointer.
Window	: Toughened / Safety glass
Sealing Ring	: Viton
Static Pressure	: 10 times of scale range.
Mounting	: Direct & Surface.
Scale Range	: 250mmWc to 6000mmWc up to 10 Kg/cm ² .

OPTIONAL FEATURES

- D P with Electrical contact available on request.
- Pressure equalizing valve available on request.
- Surface & Pipe Mounting on request.

APPLICATION

Air, Gas & Filter Application.

POINTER INSTRUMENTS PVT. LTD.

210, Phase-1, G.I.D.C. Industrial Estate, Chhatral-382 729. Tal.: Kalol, Dist.: Gandhinagar, Gujarat, INDIA.
Ph.: +91 2764-234357 | E-mail: sales@pointer.in, pointer210@yahoo.co.in, info@pointer.in | Web: www.pointer.in

